

CUSTOMER 客戶	新瑞科		LOT QTY 出貨數量	2000		INSPECTION DATE 檢驗日期		2019.4.17		
MODEL 機種	MF30060V1-1000C-1199		INSPECTING QUANTITY 檢驗數量	128		DATE CODE 週期		1		
M.O 製單號碼	645624-01		DEFECTIVE QTY 不良數量	0		OPERATIVE VOLTAGE 操作電壓		5V		
CUSTOMER P/N 客戶料號			INSPECTION LEVEL: MIL-STD-1916 VL-IV SAMPLING JUDGE: Acc./0, Rej./1 RECORD: 5Pcs			JUDGE 判定		<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Rej.		
ITEM 項目	INSPECTION ITEM 檢查項目		SPECIFICATION 規格		1	2	3	4	5	
FUNCTION 性能	1. 起動電壓 Start Voltage		≤ 2.5 V		2.2	2.3	2.3	2.2	2.3	
	2. 鎖住電流 Locked Current		210 <input type="checkbox"/> A 210 <input checked="" type="checkbox"/> MA		174	170	172	176	175	
	3. 異音/振動 Noise/Vibration		耳聽/手感 Listening/Hand feeling		OK	OK	OK	OK	OK	
	4. 死角測試 Dead Angle Test		on/off 無死角		OK	OK	OK	OK	OK	
	5. 波形 Waveform		<input checked="" type="checkbox"/> 電流波 Current wave <input type="checkbox"/> Hi-Lo波 Hi-Lo wave <input type="checkbox"/> 方波 Square wave		OK	OK	OK	OK	OK	
	<input type="checkbox"/> Duty:		電流 Current	112 ± 10%	101 - 124 <input checked="" type="checkbox"/> A 9100 ± 15% <input checked="" type="checkbox"/> mA	117	121	115	116	117
	<input type="checkbox"/> 高 High <input type="checkbox"/> 低 Low		轉速 RPM	7735 - 10465	9131	9276	9277	9197	9079	
	<input type="checkbox"/> Duty:		電流 Current							
	<input type="checkbox"/> 高 High <input type="checkbox"/> 低 Low		轉速 RPM							
	<input type="checkbox"/> Duty:		電流 Current							
	<input type="checkbox"/> 高 High <input type="checkbox"/> 低 Low		轉速 RPM							
	<input type="checkbox"/> Duty:		電流 Current							
	<input type="checkbox"/> 高 High <input type="checkbox"/> 低 Low		轉速 RPM							
	<input type="checkbox"/> Duty:		電流 Current							
	<input type="checkbox"/> 高 High <input type="checkbox"/> 低 Low		轉速 RPM							
7. 功率 Watt(僅適用AC機型) Power (Only for AC model)				W						
DIMENSION 尺寸	1. 框長/直徑 Frame Length / Diameter		30 ± 0.5 29.5 - 30.5 mm		29.96	29.93	29.95	29.98	29.93	
	2. 框寬 Frame Width		30 ± 0.5 29.5 - 30.5 mm		29.94	29.97	30.01	29.99	29.90	
	3. 框厚 Frame Thickness		6.5 ± 0.3 6.2 - 6.8 mm		6.50	6.54	6.48	6.49	6.51	
	4. 架設孔徑 Mounting hole diameter		3.2 ± 0.3 2.9 - 3.5 ∅		3.20	3.19	3.23	3.24	3.21	
	5. 導線長度 Lead wire length		145 ± 10 135 - 155 mm		144	145	145	144	145	
	6. 套管長度 Tube Length									
	7. 套管至框邊距離 Distance between tube and frame side									
	8. 套管至Housing距離 Distance between tube and Housing									
INSPECTION 目視 檢驗	1. 風扇外觀 Fan Appearance		目視 Visual inspection		OK	OK	OK	OK	OK	
	2. 線材規格 Wire Spec.		UL1571 #28 AWG		OK	OK	OK	OK	OK	
	3. 標籤核對 Label Check		SUNON		OK				OK	
	4. 包裝/穿頭 Pack/Method		20190219		OK					
	5. HSF包裝 HSF Pack		目視 Visual inspection		OK					
REMARK 註記	1. 有無理雙線槽 If handle the double wire slots		<input type="checkbox"/> 有 YES <input checked="" type="checkbox"/> 無 NO							
	2. 導線出線槽有無點膠 If add oil on lead wire which is out of slot		<input type="checkbox"/> 有 YES <input checked="" type="checkbox"/> 無 NO							
				配線簡圖 Lead wire Drawing						